

MINERAL OIL type Te 6 A
(ST 16/2005)
Custom code: 2710.19.99

TECHNICAL SPECIFICATIONS :

CHARACTERISTICS	ADMISSIBILITY CONDITIONS Te 6 A	TEST METHOD	
		STAS	ASTM
Relative density at 15 ⁰ C, max	0,900	35-81	D 1298 / 85
Flash point M, ⁰ C, min.	110	5489-80	D92 / 97
Viscosity, cSt max. - at 20 ⁰ C; - at 50 ⁰ C;	9-14 3-6	117-87	D 445 / 96
Colour ASTM max	2.5	34-67	D 1500/96
Freeze point, ⁰ C, max. - summer: - winter	+ 5 - 5	39-80	D 97 /96
Ash, %, max.	0,005	38-81	D 482 / 95
Copper strip corrosion 3h/100 ⁰ C	absent	SR ISO 2160	D 130/94
Coke, %, max.	0,1	SR ISO 6615-96	D 189 / 97
Viscosity index, min.	70	-	D 2270 / 93

GENERAL DESCRIPTION:

Present specification are referring to the mineral textile oils type Te 6 A produced from medium oil fractions , obtained by crude oil processing.

APPLICATIONS:

These products are used for greasing of industrial sewing and knitting machines, spinning mills and for greasing of silk, cotton threads to be knitted.

End users are sole responsible for not using the product in accordance with producer's prescriptions and import country legislation in force.

PACKAGING – STORAGE:

The packaging, marking and storage shall be made as per stipulations of Romanian standard STAS 4225/79.

SAFETY MEASURES:

Product has to be delivered only in clean suitable means of transportation, each lot being accompanied by quality and quantity certificates. Quality is guaranteed for 3 (three) months starting from producing date.

As product is flammable, usual caution measures of fire prevention have to be taken when handling and storing this product.

Note: The info in this technical sheet is valid until the 31st of December, 2007. Please to contact STEAUA ROMANA REFINERY in order to see if the document has been revised .