

MINERAL OIL Te 12 type A
(ST 12/2004)
Custom code: 2710.19.99

TECHNICAL SPECIFICATIONS :

CHARACTERISTICS	ADMISSIBILITY CONDITIONS	TEST METHOD		
		Te 12 A	STAS	ISO
Relative density at 20 ⁰ C, max	0,900	35-81	3675	D 1298 / 85
Viscosity at 50 ⁰ C cSt max.	6 -12	117-87	3104	D 445 / 96
Colour ASTM max	3	SRISO 2049-98	2049	D 1500/96
Flash point M, ⁰ C, min.	100	5489-80	-	D92 / 97
Freeze point, ⁰ C, max.	+ 1	39-80	-	D 97 /96
Acidity / alcalinity	absence	22-64	-	D 664 / 95
Water+ sediment % , max.	0,1	24/ 1–89	3734	D 1796/97
Coke, %, max.	0,15	SR ISO 6615	6615	D 189 / 97
Ash, %, max.	0,01	38-81	6245	D 482 / 95
Viscosity index min.	70	55 - 81	2909	D 2270 / 93

GENERAL DESCRIPTION:

Present specification are referring to the mineral textile oils Te12 type A produced from medium oil fractions , obtained by crude oil processing.

APLICATIONS:

This product is used for greasing of industrial sewing and knitting machines, spinning mills, as per equipment technical specification.

End users are sole responsible for not using the product in accordance with producer's prescriptions and import country legislation in force.

PACKAGING – STORAGE:

The packaging, marking and storage shall be made as per stipulations of Romanian standard STAS 4225/79.

SAFETY MEASURES:

Product has to be delivered only in clean suitable means of transportation, each lot being accompanied by quality and quantity certificates. Quality is guaranteed for 3 (three) months starting from producing date.

As product is flammable, usual caution measures of fire prevention have to be taken when handling and storing this product.

Note: The info in this technical sheet is valid until the 31st of December, 2007. Please contact STEAUA ROMANA REFINERY in order to see if the document has been revised .